SAFETY DATA SHEET

Date of issue : 5 February 2016 Version : 3.01



Section 1. Identification

Product code	: T491/1L
Product name	: T491 MATTING BASE
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Product use	: Coating. Paint. Painting-related materials.
Supplier's details	: PPG INDUSTRIES NEW ZEALAND LTD 5 MONAHAN ROAD, MT WELLINGTON, AUCKLAND www.ppgnz.co.nz
	Telephone Numbers: 09 573 1620, 0800 659378 021 940 920 (24 Hours)
Emergency telephone number (with hours of operation)	: POISON CENTRE: 0800 764766 (24 hours)
e-mail address of person responsible for this SDS	: ehsnz@ppg.com

Section 2. Hazards identification

HSNO Classification

: 9.3 - TERRESTRIAL VERTEBRATE ECOTOXICITY - Category C

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001. This material is not classified as a dangerous good according to criteria in New Zealand Standard 5433:2007 Transport of Dangerous Goods on Land.

<u>GHS label elements</u>		
Signal word	1	No signal word.
Hazard statements	1	Harmful to terrestrial vertebrates.
Precautionary statements		
Prevention	1	Avoid release to the environment.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Symbol	:	
Other hazards which do not result in classification	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
CAS number/other identifiers		
Product code	:	T491/1L
Hazardous ingredients		

Hazardous ingredients	%	CAS number
Silica gel, pptd., crystfree 2-butoxyethanol		112926-00-8 111-76-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. Most important symptoms/effects, acute and delayed Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion **Over-exposure signs/symptoms Eyes** : No specific data. Inhalation : No specific data. : No specific data. Skin : No specific data. Ingestion Indication of immediate medical attention and special treatment needed, if necessary Specific treatments : Not available. Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Hazchem code	: Not available.
Special precautions for fire- fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for cor	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling
 Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

New Zealand Page: 3/9

Section 7. Handling and storage

Conditions for safe storage,	: Storage temperature: 5 to 35°C (41 to 95°F). Store in accordance with local
including any	regulations. Store in original container protected from direct sunlight in a dry, cool
incompatibilities	and well-ventilated area, away from incompatible materials (see Section 10) and
	food and drink. Keep container tightly closed and sealed until ready for use.
	Containers that have been opened must be carefully resealed and kept upright to
	prevent leakage. Do not store in unlabelled containers. Use appropriate
	containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Ingredient name			Exposure limits
Silica gel, pptd., crystfree 2-butoxyethanol			EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 6 mg/m ³ 8 hours. Form: inhalable dust TWA: 2.4 mg/m ³ 8 hours. Form: respirable dust NZ OSH (New Zealand, 2/2013). Absorbed through skin. WES-TWA: 121 mg/m ³ 8 hours. WES-TWA: 25 ppm 8 hours.
Recommended monitoring procedures	:		ay be required to determine the effectiveness sures and/or the necessity to use respiratory and be made to appropriate monitoring ance documents for methods for the
Appropriate engineering controls	:	control worker exposure to airborne co ingredients with exposure limits, use pr	Good general ventilation should be sufficient to ontaminants. If this product contains rocess enclosures, local exhaust ventilation or rker exposure below any recommended or
Environmental exposure controls	:	they comply with the requirements of e	cess equipment should be checked to ensure environmental protection legislation. In some eering modifications to the process equipment to acceptable levels.
ndividual protection measur	<u>es</u>		
Hygiene measures	:	eating, smoking and using the lavatory Appropriate techniques should be used	d to remove potentially contaminated clothing. using. Ensure that eyewash stations and
Respiratory protection	:	hazards of the product and the safe we workers are exposed to concentrations appropriate, certified respirators. Use	h known or anticipated exposure levels, the orking limits of the selected respirator. If a above the exposure limit, they must use a properly fitted, air-purifying or air-fed standard if a risk assessment indicates this is

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: butyl rubber
Eye protection	: Safety glasses with side shields.
Skin protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	: Liquid.	
Colour	: Clear.	
Odour	: Faint odour.	
Odour threshold	: Not available.	
рН	: Not available.	
Melting point	: Not available.	
Boiling point	: >37.78°C (>100°F)	
Flash point	: Closed cup: 100°C (212°F) [Product does not sustain combustion.]	
Burning time	: Not applicable.	
Burning rate	: Not applicable.	
Material supports combustion.	: No.	
Flammability (solid, gas)	: Not available.	
Lower and upper explosive (flammable) limits	: Lower: 1% Upper: 11%	
Vapour pressure	: Not available.	
Relative density	: 1.05	
Bulk Density (g/cm³)	: 1.05	
Solubility	: Partially soluble in the following materials: cold water.	
Solubility in water at room temperature (g/l):	: Not available.	
Partition coefficient: n- octanol/water	: Not available.	
Auto-ignition temperature	: Not available.	
Decomposition temperature	: Not available.	
SADT	: Not available.	
Viscosity	: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)	
Viscosity	: < 30 s (ISO 6mm)	

New Zealand Page: 5/9

Product code T491/1L

Product name T491 MATTING BASE

Section 10. Stability and reactivity

Stability	: Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials strong acids strong alkalis
Hazardous decomposition products	 Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerisation	: Under normal conditions of storage and use, hazardous polymerisation will not occur.

Section 11. Toxicological information

Information on the likely routes of exposure			
Inhalation	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Eye contact	: No known significant effects or critical hazards.		
Symptoms related to t	he physical, chemical and toxicological characteristics		
Inhalation	: No specific data.		
Ingestion	: No specific data.		
Skin contact	: No specific data.		
Eye contact	: No specific data.		

Delayed and immediate effects and also chronic effects from short and long term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LD50 Dermal	Rabbit	1060 mg/kg	-
-	LD50 Oral	Rat	470 mg/kg	-
Conclusion/Summary	: There are no data avai	lable on the mixture its	self.	
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data avai	lable on the mixture it	self.	
Eyes	: There are no data available on the mixture itself.			
Respiratory	: There are no data available on the mixture itself.			
<u>Sensitisation</u>				
Conclusion/Summary				
Skin	: There are no data available on the mixture itself.			
Respiratory	: There are no data available on the mixture itself.			
Potential chronic health eff	<u>ects</u>			
General	: No known significant et	fects or critical hazard	ds.	
Carcinogenicity	: No known significant effects or critical hazards.			
Mutagenicity	: No known significant et	fects or critical hazard	ds.	
Teratogenicity	: No known significant effects or critical hazards.			

Section 11. Toxicological information

Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Chronic toxicity	
Not available.	
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Not available.	
Appiration beyond	

Aspiration hazard

Not available.

Numerical measures of toxicity

Acute toxicity estimates

ATE value
9447.9 mg/kg 6030.6 mg/kg 221.1 mg/l

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

Section 12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic	and	terrestrial	toxicity

Product/ingredient name	Result	Species	Exposure
Silica gel, pptd., crystfree	NOEC >1000 ppm Acute NOEC >10000 ppm Fresh water Acute NOEC >10000 ppm	Daphnia - Daphnia magna Fish Fish - Brachydanio rerio	24 hours 96 hours Static 4 days Static

Persistence/degradability

Product code T491/1L

Product name T491 MATTING BASE

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Silica gel, pptd., crystfree 2-butoxyethanol	-	-	Not readily Readily
Bioaccumulative potential			
Product/ingredient name	LogPow	BCF	Potential

Product/ingredient name	LogPow	BCF	Potential
Silica gel, pptd., crystfree	-	0	low
2-butoxyethanol	0.81	-	low

Mobility in soil

wobinty in son	
Soil/water partition coefficient (Koc)	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

Do not allow to enter drains or watercourses.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
Not ouitable:	Do not allow to optor drains or watercourses

Not suitable: : Do not allow to enter drains or watercourses.

The classification of the product may meet the criteria for a hazardous waste. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	NZ	ADG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

New Zealand Page: 8/9

Product code T491/1L

Product name T491 MATTING BASE

14. Transport information

Additional information

NZ	: None identified.
ADG	: None identified.
Hazchem code	: Not applicable.
IMDG	: None identified.
IATA	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
HSNO Approval Number	: HSR002670 Subsidiary Hazard
Emergency Management Regulations	: Level 1: Not applicable.
	Level 2: MSDS required when any amount is present in a workplace. Level 3: Not applicable.
	Ecotoxic Signage required when 10000L is present in a workplace.
Approved Handler	: Not applicable.

Section 16. Other information

Date of issue	:	5 February 2016
Indicates information that has changed from previously issued version.		
Key to abbreviations		STEL = Short Term Exposure Limit TWA = Time-Weighted Average WES = Work Exposure Standard
References Organisation that prepared the MSDS	- T	Not available. EHS

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.