#RSC

SAFETY DATA SHEET

1. Identification

Product identifier Gunk Carburetor Parts Cleaner

Other means of identification

SDS number CC3K Part No. CC3K

Tariff code 3814.00.5090

Recommended use Parts Cleaner
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company nameRSC Chemical SolutionsAddress600 Radiator Road

Indian Trail, NC 28079

United States

Telephone Customer Service: (704) 821-7643

Technical: (704) 684-1811

Website www.rscbrands.com

E-mail Not available.

Emergency phone number Emergency Telephone: (303) 623-5716

Emergency Contact: RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 4Acute toxicity, inhalationCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Serious eye damage/eye irritation Category 2A
Sensitization, respiratory Category 1
Sensitization, skin Category 1
Germ cell mutagenicity Category 1
Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 2

Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements

Environmental hazards



Signal word Danger

Material name: Gunk Carburetor Parts Cleaner
CC3K Version #: 02 Revision date: 06-19-2015 Issue date: 05-01-2015

Hazard statement

Combustible liquid. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

29.45% of the mixture consists of component(s) of unknown acute oral toxicity. 23.87% of the mixture consists of component(s) of unknown acute inhalation toxicity. 44.15% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 42.47% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| Petroleum naphtha | | 64742-94-5 | 30 - < 40 |
| 2-Butoxyethanol | | 111-76-2 | 20 - < 30 |
| Tert-butylbenzene | | 98-06-6 | 5 - < 10 |
| 1,2,3-trimethylbenzene | | 526-73-8 | 1 - < 3 |
| 1,4-diethylbenzene | | 105-05-5 | 1 - < 3 |
| NAPHTHALENE | | 91-20-3 | 1 - < 3 |
| Triéthanolamine | | 102-71-6 | 1 - < 3 |
| DIETHANOLAMINE | | 111-42-2 | < 1 |
| Diethylbenzene | | 25340-17-4 | < 1 |
| Other components below reportable levels | 3 | | 30 - < 40 |

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER

or doctor/physician.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Material name: Gunk Carburetor Parts Cleaner

Ingestion

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Specific hazards arising from the chemical

mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire. and precautions for firefighters

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

The product is combustible, and heating may generate vapors which may form explosive vapor/air

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

| Components | Туре | Value | |
|------------------------------------|----------------------------|-----------|------------------------|
| 2-Butoxyethanol (CAS I11-76-2) | PEL | 240 mg/m3 | |
| , | | 50 ppm | |
| NAPHTHALENE (CAS | PEL | 50 mg/m3 | |
| 91-20-3) | | 10 ppm | |
| Petroleum naphtha (CAS | PEL | 400 mg/m3 | |
| 64742-94-5) | . == | . e ege | |
| | | 100 ppm | |
| US. ACGIH Threshold Limit Value | es | | |
| Components | Туре | Value | Form |
| 1,2,3-trimethylbenzene | TWA | 25 ppm | |
| (CAS 526-73-8) | | | |
| 2-Butoxyethanol (CAS 111-76-2) | TWA | 20 ppm | |
| DIETHANOLAMINE (CAS | TWA | 1 mg/m3 | Inhalable fraction and |
| 111-42-2) | | - | vapor. |
| NAPHTHALENE (CAS | TWA | 10 ppm | |
| 91-20-3) Petroleum naphtha (CAS | TWA | 200 mg/m3 | Non-aerosol. |
| 64742-94-5) | IVVA | 200 mg/m3 | Non-acrosor. |
| Triéthanolamine (CAS | TWA | 5 mg/m3 | |
| 102-71-6) | | | |
| US. NIOSH: Pocket Guide to Che | | | |
| Components | Туре | Value | |
| 1,2,3-trimethylbenzene | TWA | 125 mg/m3 | |
| (CAS 526-73-8) | | 05 | |
| 2 Dutawyathanal (CAS | TWA | 25 ppm | |
| 2-Butoxyethanol (CAS 111-76-2) | IVVA | 24 mg/m3 | |
| | | 5 ppm | |
| DIETHANOLAMINE (CAS | TWA | 15 mg/m3 | |
| 111-42-2) | | | |
| NADUTUAL ENE (CAC | OTEL | 3 ppm | |
| NAPHTHALENE (CAS 91-20-3) | STEL | 75 mg/m3 | |
| o. 20 0) | | 15 ppm | |
| | TWA | 50 mg/m3 | |
| | | 10 ppm | |
| US. Workplace Environmental Ex | posure Level (WEEL) Guides | | |
| Components | Type | Value | |
| 1,4-diethylbenzene (CAS | TWA | 5 ppm | |
| 105-05-5) | 1 **/ 1 | о ррш | |
| Diethylbenzene (CAS | TWA | 5 ppm | |
| 25340-17-4) | | | |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------------|----------|--|---------------------|---------------|
| 2-Butoxyethanol (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | * |

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

DIETHANOLAMINE (CAS 111-42-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

DIETHANOLAMINE (CAS 111-42-2)

NAPHTHALENE (CAS 91-20-3)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Clear. Liquid.

Physical state Liquid.
Form Liquid.
Color Pale yellow
Odor Aromatic.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -102.64 °F (-74.8 °C) estimated Initial boiling point and boiling 335.12 °F (168.4 °C) estimated

range

Flash point 143.0 °F (61.7 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit - upper

5 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.36 hPa estimated

Vapor density Not available.

Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient**

(n-octanol/water)

460.4 °F (238 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 7.70 lbs/gal estimated

Explosive properties Not explosive.

Combustible IIIA estimated Flammability class

Oxidizing properties Not oxidizing. Percent volatile 43 % estimated Specific gravity 0.92 estimated VOC (Weight %) 41 % w/w

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid

flash point. Contact with incompatible materials.

Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by Inhalation

inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause allergy

or asthma symptoms or breathing difficulties if inhaled.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Strong oxidizing agents.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact Causes serious eve irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May

cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful if swallowed. Narcotic effects. May cause an allergic skin reaction.

May cause respiratory irritation.

Species Test Results Components

1,2,3-trimethylbenzene (CAS 526-73-8)

Acute Oral

LD50 Rat 8970 mg/kg

Material name: Gunk Carburetor Parts Cleaner

Components Species Test Results

2-Butoxyethanol (CAS 111-76-2)

Acute
Dermal
LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours

Rat 450 ppm, 4 Hours

Oral

LD50 Guinea pig 1.2 g/kg

 Mouse
 1.2 g/kg

 Rabbit
 0.32 g/kg

 Rat
 560 mg/kg

DIETHANOLAMINE (CAS 111-42-2)

Acute Dermal

LD50 Rabbit 11.9 ml/kg

Oral

LD50 Rat 710 mg/kg

NAPHTHALENE (CAS 91-20-3)

Acute Dermal

LD50 Rabbit > 2 g/kg

Rat > 20 g/kg

Oral

LD50 Guinea pig 1200 mg/kg

Rat 490 mg/kg

Petroleum naphtha (CAS 64742-94-5)

Acute Inhalation

LC50 Rat 61 mg/l, 4 Hours

Oral

LD50 Rat > 25 ml/kg

Triéthanolamine (CAS 102-71-6)

Acute Dermal

LD50 Rabbit

Rabbit > 20000 mg/kg

Oral

LD50 Guinea pig 5300 mg/kg

Rat 8 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity Suspected of causing cancer.

^{*} Estimates for product may be based on additional component data not shown.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

DIETHANOLAMINE (CAS 111-42-2) 2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans. NAPHTHALENE (CAS 91-20-3)

Triéthanolamine (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

NAPHTHALENE (CAS 91-20-3) Reasonably Anticipated to be a Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not an aspiration hazard.

May cause damage to organs through prolonged or repeated exposure. May be harmful if **Chronic effects**

absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged exposure may cause chronic effects.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

| Components | | Species | Test Results |
|----------------------|----------------|---|------------------------------|
| 2-Butoxyethanol (CAS | 3 111-76-2) | | |
| Aquatic | | | |
| Fish | LC50 | Inland silverside (Menidia beryllina) | 1250 mg/l, 96 hours |
| DIETHANOLAMINE (| CAS 111-42-2) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Ceriodaphnia dubia) | 61.8 - 86.04 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 100 mg/l, 96 hours |
| NAPHTHALENE (CAS | S 91-20-3) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 1.09 - 3.4 mg/l, 48 hours |
| Fish | LC50 | Pink salmon (Oncorhynchus gorbuscha) | 1.11 - 1.68 mg/l, 96 hours |
| Petroleum naphtha (C | AS 64742-94-5) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia pulex) | 2.7 - 5.1 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours |
| | | | 8.8 mg/l, 96 hours |
| Triéthanolamine (CAS | 3 102-71-6) | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Ceriodaphnia dubia) | 565.2 - 658.3 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 10610 - 13010 mg/l, 96 hours |

^{*} Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Material name: Gunk Carburetor Parts Cleaner

CC3K Version #: 02 Revision date: 06-19-2015 Issue date: 05-01-2015

Partition coefficient n-octanol / water (log Kow)

1,4-diethylbenzene 4.45 2-Butoxyethanol 0.83 **DIETHANOLAMINE** -1.43**NAPHTHALENE** 3.3 Tert-butylbenzene 4.11 Triéthanolamine -1

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Consumer commodity

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number Not available.

UN proper shipping name

Transport hazard class(es)

Class ORM-D

Subsidiary risk Label(s) None

Not applicable.

Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 156, 306 156, 306 Packaging non bulk Packaging bulk None

IATA

UN number ID8000

UN proper shipping name Consumer commodity

Transport hazard class(es)

Class 9 Subsidiary risk

Packing group Not applicable.

Environmental hazards No. 9L **FRG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

IMDG

UN number UN1223

UN proper shipping name

Transport hazard class(es)

KEROSENE SOLUTION (Petroleum naphtha)

3 Class Subsidiary risk Ш Packing group

Material name: Gunk Carburetor Parts Cleaner

Environmental hazards

Marine pollutant No. F-E, S-E **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

IATA



IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2) Listed. **DIETHANOLAMINE (CAS 111-42-2)** Listed. NAPHTHALENE (CAS 91-20-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. | |
|-----------------|------------|-----------|--|
| 2-Butoxyethanol | 111-76-2 | 20 - < 30 | |
| NAPHTHALENE | 91-20-3 | 1 - < 3 | |
| DIETHANOLAMINE | 111-42-2 | < 1 | |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

DIETHANOLAMINE (CAS 111-42-2)

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

1,2,3-trimethylbenzene (CAS 526-73-8)

2-Butoxyethanol (CAS 111-76-2)

DIETHANOLAMINE (CAS 111-42-2)

NAPHTHALENE (CAS 91-20-3)

Petroleum naphtha (CAS 64742-94-5)

Tert-butylbenzene (CAS 98-06-6)

US. Massachusetts RTK - Substance List

1,2,3-trimethylbenzene (CAS 526-73-8)

1,4-diethylbenzene (CAS 105-05-5)

2-Butoxyethanol (CAS 111-76-2)

DIETHANOLAMINE (CAS 111-42-2)

NAPHTHALENE (CAS 91-20-3)

Tert-butylbenzene (CAS 98-06-6)

Triéthanolamine (CAS 102-71-6)

US. New Jersey Worker and Community Right-to-Know Act

1,2,3-trimethylbenzene (CAS 526-73-8)

1,4-diethylbenzene (CAS 105-05-5)

2-Butoxyethanol (CAS 111-76-2)

DIETHANOLAMINE (CAS 111-42-2)

Diethylbenzene (CAS 25340-17-4)

NAPHTHALENE (CAS 91-20-3)

Petroleum naphtha (CAS 64742-94-5)

Tert-butylbenzene (CAS 98-06-6)

Triéthanolamine (CAS 102-71-6)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,3-trimethylbenzene (CAS 526-73-8)

1,4-diethylbenzene (CAS 105-05-5)

2-Butoxyethanol (CAS 111-76-2)

DIETHANOLAMINE (CAS 111-42-2)

NAPHTHALENE (CAS 91-20-3)

Tert-butylbenzene (CAS 98-06-6)

Triéthanolamine (CAS 102-71-6)

US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2)

DIETHANOLAMINE (CAS 111-42-2)

NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

DIETHANOLAMINE (CAS 111-42-2) Listed: June 22, 2012 NAPHTHALENE (CAS 91-20-3) Listed: April 19, 2002

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

 Issue date
 05-01-2015

 Revision date
 06-19-2015

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Product Uses

Hazard(s) identification: Hazard(s) not otherwise classified (HNOC)

Physical and chemical properties: Color Transport information: General information

Material name: Gunk Carburetor Parts Cleaner

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).