

# SAFETY DATA SHEET

**Honeywell**  
**Fluka™**

F05120 Charcoal powder PUR ,250K##

**000000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Activated charcoal

Number : 000000020413

Product Use Description : Laboratory chemicals

Manufacturer or supplier's details : Honeywell International Inc.  
1953 South Harvey Street  
Muskegon, MI 49442

For more information call : 1-800-368-0050  
+1-231-726-3171  
(Monday-Friday, 9:00am-5:00pm)

**In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414**  
: **Transportation (CHEMTREC): 1-800-424-9300 or**  
: **+1-703-527-3887**  
:  
: (24 hours/day, 7 days/week)

## SECTION 2. HAZARDS IDENTIFICATION

### Emergency Overview

Form : powder

Color : black

Odor : odourless

### Classification of the substance or mixture

Classification of the substance : Combustible dust  
or mixture

### GHS Label elements, including precautionary statements

Signal word : Warning

Hazard statements : May form combustible dust concentrations in air.

# SAFETY DATA SHEET



F05120 Charcoal powder PUR ,250K##

**00000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

Precautionary statements : **Prevention:**  
Use personal protective equipment as required.

Hazards not otherwise classified : Repeated or prolonged exposure may irritate eyes, skin and respiratory system.  
Activated carbon may lower oxygen content in the surrounding air, which can cause rapid suffocation in an enclosed or confined space. Ventilate space and check for sufficient oxygen content before entering.

### Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
Carbon	7440-44-0	100.00 %

## SECTION 4. FIRST AID MEASURES

General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

Inhalation : Remove to fresh air. If respiratory problems develop, obtain medical attention.

Skin contact : Wash off with soap and plenty of water. If skin irritation persists, call a physician.

Eye contact : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, consult a physician.

Ingestion : Do NOT induce vomiting. Drink at least 2 glasses of water. Never give anything by mouth to an unconscious person.

# SAFETY DATA SHEET

**Honeywell**  
**Fluka™**

**F05120 Charcoal powder PUR ,250K##**

**000000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

Consult a physician.

## Notes to physician

Treatment : Treat symptomatically.

## SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder

Specific hazards during firefighting : Avoid dust formation in confined areas.  
Airborne dusts of this product in an enclosed space and in the presence of an ignition source may constitute an explosion hazard.  
Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of dust, e.g. on floors and ledges.  
Static charges on powders or powders in liquids may ignite combustible atmospheres.  
Hazardous decomposition products formed under fire conditions.

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Provide adequate ventilation.  
May form explosive dust-air mixture.  
Avoid dust formation.  
Accumulations of dust from this product in the workplace may increase the likelihood or severity of an explosion.  
Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of dust, e.g. on floors and ledges.

# SAFETY DATA SHEET

**Honeywell**  
**Fluka™**

**F05120 Charcoal powder PUR ,250K##**

**000000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

- Eliminate all ignition sources if safe to do so.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.
- Methods for cleaning up : Avoid dust formation and electrical charging (sparking) because dust explosion might occur.  
Do not create a powder cloud by using a brush or compressed air.  
Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).  
Use only non-sparking tools.

## SECTION 7. HANDLING AND STORAGE

### Handling

- Handling : Wear personal protective equipment.  
Avoid dust formation.  
Floors, walls and other surfaces must be regularly cleaned.  
The material can accumulate static charge and can therefore cause electrical ignition.  
Static charges on powders or powders in liquids may ignite combustible atmospheres.  
Take precautionary measures against static discharges.
- Advice on protection against fire and explosion : All combustible solids have the potential to create a dust explosion hazard. The likelihood of an explosion can be dependent upon many factors, such as the explosive characteristics of the material, the design of the facility, and the manner in which the material is handled. A more detailed discussion can be found in NFPA Bulletin 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids."

### Storage

- Requirements for storage areas and containers : Store in original container.  
Keep containers tightly closed in a dry, cool and well-ventilated place.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

# SAFETY DATA SHEET



F05120 Charcoal powder PUR ,250K##

**00000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.  
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.  
Avoid breathing dust.
- Engineering measures : Provide exhaust ventilation if dust is formed.  
Use only in an area equipped with explosion proof exhaust ventilation.  
Electrical equipment should be protected to the appropriate standard.  
If formation of dust is observed, equipment has to be switched off, cleaned and serviced.
- Eye protection : Safety glasses with side-shields
- Hand protection : Latex gloves  
Gloves must be inspected prior to use.  
Replace when worn.
- Skin and body protection : Protective suit
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hygiene measures : Take off all contaminated clothing immediately.  
Remove and wash contaminated clothing before re-use.  
Keep working clothes separately.  
Wash hands before breaks and at the end of workday.  
When using, do not eat, drink or smoke.

### Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Carbon	7440-44-0	TWA : Time weighted average	10 mg/m3	03 2014	ACGIH:US. ACGIH Threshold Limit Values
Further information	: Form of exposure : Inhalable particles.				

Carbon	7440-44-0	TWA : Time weighted average	3 mg/m3	03 2014	ACGIH:US. ACGIH Threshold Limit Values
Further	: Form of exposure : Respirable particles.				

SAFETY DATA SHEET



F05120 Charcoal powder PUR ,250K##

00000020413

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

information	
-------------	--

Carbon	7440-44-0	TWA : Time weighted average	2 mg/m3	2008	ACGIH:US. ACGIH Threshold Limit Values
--------	-----------	--------------------------------	---------	------	--

Further information	:	Form of exposure : Respirable fraction.
---------------------	---	---

Carbon	7440-44-0	REL : Recomm ended exposure limit (REL):	2.5 mg/m3	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
--------	-----------	---	-----------	------	---

Further information	:	Form of exposure : Respirable.
---------------------	---	--------------------------------

Carbon	7440-44-0	PEL : Permissi ble exposure limit	15 mg/m3	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
--------	-----------	--------------------------------------	----------	------------	--

Further information	:	Form of exposure : Total dust.
---------------------	---	--------------------------------

Carbon	7440-44-0	PEL : Permissi ble exposure limit	5 mg/m3	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
--------	-----------	--------------------------------------	---------	------------	--

Further information	:	Form of exposure : Respirable fraction.
---------------------	---	---

Carbon	7440-44-0	PEL : Permissi ble exposure limit	15 mg/m3	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
--------	-----------	--------------------------------------	----------	------------	--

Further information	:	Form of exposure : Total dust.
---------------------	---	--------------------------------

## SAFETY DATA SHEET

**Honeywell**  
**Fluka™**

F05120 Charcoal powder PUR ,250K##

**00000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

Carbon	7440-44-0	PEL : Permissible exposure limit	5 mg/m3	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
--------	-----------	---	---------	------------	--

Further information	:	Form of exposure : Respirable fraction.			
---------------------	---	---	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	5 mg/m3	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------	-----------	--------------------------------------	---------	------	---

Further information	:	Form of exposure : Respirable fraction.			
---------------------	---	---	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	2.5 mg/m3	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------	-----------	--------------------------------------	-----------	------	---

Further information	:	Form of exposure : Respirable dust.			
---------------------	---	-------------------------------------	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	10 mg/m3	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------	-----------	--------------------------------------	----------	------	---

Further information	:	Form of exposure : Total dust.			
---------------------	---	--------------------------------	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	5 mg/m3	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------	-----------	--------------------------------------	---------	------	---

Further information	:	Form of exposure : Respirable fraction.			
---------------------	---	---	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	15 mg/m3	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------	-----------	--------------------------------------	----------	------	---

Further information	:	Form of exposure : Total dust.			
---------------------	---	--------------------------------	--	--	--

**SAFETY DATA SHEET**



**F05120 Charcoal powder PUR ,250K##**

**00000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

Carbon	7440-44-0	TWA : Time weighted average	15 millions of particles per cubic foot of air	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
--------	-----------	--------------------------------------	--	------	--

Further information	:	Form of exposure : Respirable fraction.			
---------------------	---	---	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	15 mg/m3	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
--------	-----------	--------------------------------------	----------	------	--

Further information	:	Form of exposure : Total dust.			
---------------------	---	--------------------------------	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	5 mg/m3	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
--------	-----------	--------------------------------------	---------	------	--

Further information	:	Form of exposure : Respirable fraction.			
---------------------	---	---	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	50 millions of particles per cubic foot of air	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
--------	-----------	--------------------------------------	--	------	--

Further information	:	Form of exposure : Total dust.			
---------------------	---	--------------------------------	--	--	--

Carbon	7440-44-0	TWA : Time weighted average	15 millions of particles per cubic foot of air	2000	Z3:US. OSHA Table Z-3 (29 CFR 1910.1000)
--------	-----------	--------------------------------------	--	------	--

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : powder

Color : black

Odor : odourless

pH : 6 - 9

Note: suspension



# SAFETY DATA SHEET

**Honeywell**  
**Fluka™**

**F05120 Charcoal powder PUR ,250K##**

**00000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

Melting point/freezing point : Note: Not applicable

Boiling point/boiling range : Note: Not applicable

Flash point : Note: Not applicable

Flammability : May form combustible dust concentrations in air.

Lower explosion limit : Note: Not applicable

Upper explosion limit : Note: Not applicable

Vapor pressure : Note: Not applicable

Density : Note: no data available

Water solubility : Note: insoluble

Ignition temperature : > 240 °C

Decomposition temperature : Note: No decomposition if used as directed.

Molecular weight : 12.01 g/mol

Bulk density : ca. 350 kg/m<sup>3</sup>

## SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under recommended storage conditions.

# SAFETY DATA SHEET

**Honeywell**  
**Fluka™**

**F05120 Charcoal powder PUR ,250K##**

**000000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

Possibility of hazardous reactions : Hazardous polymerisation does not occur.  
Conditions to avoid : Keep away from heat and sources of ignition.  
Avoid dust formation and electrical charging (sparking) because dust explosion might occur.

Incompatible materials to avoid : Strong acids and oxidizing agents  
Bases

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide

## SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50: > 2,000 mg/kg  
Species: Rat, female  
Method: OECD 423  
Note: No deaths

Acute inhalation toxicity : Note: no data available

Acute dermal toxicity : Note: no data available

Skin irritation : Species: Rabbit  
Result: No skin irritation  
Method: OECD Test Guideline 404

Eye irritation : Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405

Sensitisation : Species: Mouse  
Result: non-sensitizing  
Method: OECD Test Guideline 429

## SECTION 12. ECOLOGICAL INFORMATION

# SAFETY DATA SHEET



F05120 Charcoal powder PUR ,250K##

**000000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

## Ecotoxicity effects

Toxicity to fish : Note: no data available

Toxicity to daphnia and other aquatic invertebrates : Note: no data available

Toxicity to algae : Note: no data available

## Further information on ecology

## SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

## SECTION 14. TRANSPORT INFORMATION

**DOT** Not dangerous goods

**TDG** Not dangerous goods

**IATA** Not dangerous goods

**IMDG** Not dangerous goods

All grades of powdered activated carbon are steam activated and are not regulated for domestic or international transportation.

## SECTION 15. REGULATORY INFORMATION

### Inventories

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection : All components of this product are on the Canadian DSL

# SAFETY DATA SHEET



**F05120 Charcoal powder PUR ,250K##**

**000000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

Act (CEPA). Domestic  
Substances List (DSL)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical  
Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic  
Substances and Hazardous  
and Nuclear Waste Control  
Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing  
Chemical Substances : On the inventory, or in compliance with the inventory

New Zealand. Inventory of  
Chemicals (NZIoC), as  
published by ERMA New  
Zealand : On the inventory, or in compliance with the inventory

## National regulatory information

**SARA 302 Components** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313 Components** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**SARA 311/312 Hazards** : Acute Health Hazard

**California Prop. 65** : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**Massachusetts RTK** : Carbon 7440-44-0

**New Jersey RTK** : Carbon 7440-44-0

**Pennsylvania RTK** : Carbon 7440-44-0

# SAFETY DATA SHEET

**Honeywell**  
**Fluka™**

F05120 Charcoal powder PUR ,250K##

**000000020413**

Version 1.0

Revision Date 10/02/2016

Print Date 10/03/2018

## SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	1
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group