Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex (877) 376-2839 Emergency: 800-255-3924 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name:QUICK ORANGE GLASS CLEANER 18.750Z AEItem No:82544Product Type:Aerosol cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS				
Ingredient	Weight Percent	ACGIH TLV: TWA	OSHA PEL:	
WATER 7732-18-5	>80	Not Listed	Not Listed	
2-PROPANOL 67-63-0	<10	200 ppm TWA	400 ppm TWA; 980 mg/m ³ TWA	
BUTANE 106-97-8	<5	1000 ppm TWA	800 ppm TWA; 1900 mg/m ³ TWA	
2-BUTOXYETHANOL 111-76-2	<5	20 ppm TWA	25 ppm TWA; 240 mg/m ³ TWA	
PROPANE 74-98-6	<5	1000 ppm TWA	1000 ppm TWA; 1800 mg/m ³ TWA	

3. HAZARDS IDENTIFICATION

Toxicity:

May cause eye, skin and respiratory irritation. Excessive inhalation causes headache, dizziness, nausea, and incoordination. Eye and skin contact, ingestion, inhalation

Primary Routes of Entry: Signs and Symptoms of Exposure:

Overexposure may cause eye and skin redness. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
2-PROPANOL 67-63-0	<10		A4 - Not classifiable as a human	Group 3 Monograph 71, 1999; Supp.7, 1987;
			carcinogen	Monograph 15, 1977
2-BUTOXYETHANOL 111-76-2	<5	male rat-no evidence; female rat-equivocal evidence; male mice- some evidence; female mice-some evidence		Group 3; Vol.88, 2004

Medical Conditions Recognized as None known Being Aggravated by Exposure:

4. FIRST AID MEASURES

Ingestion: Inhalation: Skin Contact: Eye Contact: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention. Wash off with soap and water. If skin irritation persists, call a physician. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Recommended Extinguishing Media: Special Fire-Fighting Procedures:

Hazardous Products of Combustion: Unusual Fire/Explosion Hazards: No flame projection Carbon Dioxide, Dry Chemicals, Foam. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Oxides of carbon Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Do not puncture or incinerate container.

5. FIRE FIGHTING MEASURES

Lower Explosive Limit: Upper Explosive Limit: Not determined. Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst. Store in accordance with NFPA 30B for Level 1 Aerosols. Do not use near heat, sparks or open flame. Do not puncture or incinerate container.

Handling:

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses
Skin:	Not normally required when using an aerosol.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection:	Not required under normal use. An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White foam
Odor:	Orange
Boiling Point:	>200° F
pH:	10.0-10.5
Solubility in Water:	SOLUBLE
Specific Gravity:	0.98-0.99
VOC Content(Wt.%):	10 % by weight
Vapor Pressure:	Not determined
Vapor Density (Air=1):	Heavier than air
Evaporation Rate:	<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Hazardous Polymerization: Incompatabilities: Conditions to Avoid: Hazardous Products of Combustion: Stable at normal conditions Will not occur. Strong oxidizers Keep away from heat, sparks and open flame. - No smoking, Freezing Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:Dispose of in accordance with local, state and federal regulations. This container may be recycled in
aerosol recycling centers. Before offering for recycling, empty the can by using the product according to
the label. If recycling is not available, wrap the container and discard in the trash.US EPA Waste Number:D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172) <u>Domestic Ground Transport</u> DOT Shipping Name: Hazard Class: UN/ID Number:

Consumer Commodity (not more than one liter) ORM-D None

14. TRANSPORTATION INFORMATION None

Marine Pollutant:

ΙΑΤΑ

Proper Shipping Name:	Consumer Commodity (Not more than 1 liter)
Class or Division:	Class 9
UN/NA Number:	ID 8000

IMDG

Proper Shipping: Hazard Class: **UN Number:**

Aerosols, Limited Quantity Class 2.2 UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

2-BUTOXYETHANOL

CALIFORNIA PROP 65: No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0 HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0 Estimated HMIS Classification: NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:	Denise Boyd, Health and Safety Manager			Revision Date: February/23/2007				
Company:	Permatex. Inc.	10 Columbus Blvd.	Hartford,	CT USA 06	106	Revision	4	
						Number:		